



Automatic Systems Monitor Kit

- Bilge Water Level
- Engine Temperature
- Cooling Water Flow
- Fire
- Oil pressure



20001 ASM 12-S Single Engine, 12 volt
20002 ASM 24-S Single Engine, 24 volt
20012 ASM 32-S Single Engine, 32 volt
 Kit includes 5 detectors, 1 pc board, 1 indicator panel, 1 bell

20003 ASM 12-T Twin Engine, 12 volt
20004 ASM 24-T Twin Engine, 24 volt
20014 ASM 32-T Twin Engine, 32 volt
 Kit includes 10 detectors, 2 pc boards, 1 indicator panel, 1 bell



Smart Bilge Pump Switch

- Switches Pump ON and OFF
- Pumps additional 15 seconds to completely clear the bilge
- Warns of excessive pumping
- Handles pumps up to 30 Amps

20038 SS-209-12 12 volt
20039 SS-209-24 24 volt
20040 SS-209-32 32 volt

Automatic Bilge Pump System

- Switches pump ON and OFF
- Pumps Additional 15 seconds to completely clear the bilge
- Warns of excessive pumping
- Handles pumps up to 30 Amps

20035 SS-208-12 12 volt
20036 SS-208-24 24 volt
20037 SS-208-32 32 volt



Save-Your-Engine Kit

- Monitors raw water flow
- Sounds alarm and activates a red light if flow stops
- One kit covers 1/2" through 1-1/2" hose size by using hose to barb adapters

20064 1/2" through 1-1/2" hose size
20063 2" hose size



4-3/4" x 3-7/8"

Bilge Pump Monitor

- Green power ON light Red light to indicate bilge pump is pumping
- Built-in Pump Counter
- Activates loud alarm if pump stays on longer than two minutes—**when used with Aqualarm SS-209**
- Can be used with any pump switch as a high water alarm
- AUTO/OFF/MAN (test) switch MUTE SWITCH

20043 12 volt **20046** 24 volt **20047** 32 volt



3-1/2" x 3"

Bilge Pump Alarm

- Green power ON light Red light to indicate bilge pump is pumping
- Activates loud alarm if pump stays on longer than two minutes—**when used with Aqualarm SS-209**
- Can be used with any pump switch as a high water alarm
- AUTO/OFF/MAN (test) switch

20042 12 volt
20057 24 volt
20058 32 volt



3" x 2-1/2"

Bilge Pump Counter

- Electronically counts number of times bilge pump switches
- Bright LED digital readout with RESET
- Retains count until reset
- Can be used with all types of water pumps

20045 12, 24, 32 volt



Bilge Water Level Warning System

- Loud bell and red light panel signal HIGH WATER
- Includes bell, bilge water level detector and red light warning panel

20131 RBWS-12 12 volt
 20132 RBWS-24 24 volt
 20133 RBWS-32 32 volt



Boat Security System

- Infrared motion detector
- Programmable entry and exit code
- Waterproof exterior siren
- Red light warning panel
- PC board for wiring

20010 BSS-12 12 volt



4-1/2" x 3" x 2"

Last Watch II

- Digit Helmsman Minder
- LED displays countdown time
- Loud alarm sounds if not reset
- Key lock for security
- Can be use as enclosure or flush mount

20011 12, 24, 32 volts



4-1/2" x 3"



3" x 1-3/4"

Exhaust Overheat Alarm

- Activates warning panel if wet exhaust exceeds 200 ° F
- Adjustable aluminum band fits 2" to 8" exhaust
- Green power ON light and RED warning light
- Five feet of Marine Grade Tinned Wire

20245 Exhaust Overheat Alarm (Detector and Panel)
 20250 Exhaust Overheat Detector (12, 24, 32 volt)
 20251 Exhaust Warning Panel (12 volt only)



3-3/4" x 4-3/4"

Fire Monitor

- Monitors up to five areas
- Audible alarm with mute
- Red warning light
- Test button
- Coast Guard accepted

20070 Fire Monitor with one Fire Detector

Specific Systems Monitors

Individual alarm systems for critical areas - All systems include warning panel and detector - Available black or white

All panels 3" x 1-3/4"



20230 20234 20232 20236



20240 20242



20210 20214 20212 20216



20220 20222



Bait Tank Alarm

- Monitors water flow to bait tank
- Sounds alarm and lights red light if flow stops
- One kit Fits 1/2" through 1-1/2" pipe sizes (2" available)

20050 Bait Tank Alarm for 1/2" through 1-1/2"
 20052 Bait Tank Alarm for 2"



200 Series

Cooling Water Flow Detectors

- Monitors raw water flow
 - Activates audible or visual alarm
- | | | |
|--------------|---------|-------------------------------------|
| 10231 | 200 | 2" Female Pipe Thread |
| 10271 | 206 | 1-1/2" Female Pipe Threads |
| 10233 | 210 | 1" Female Pipe Threads |
| 13209 | 306-LF | 1" Female Pipe Threads - Low Flow |
| 13212 | 306-ADJ | 1" Female Pipe Threads - Adjustable |



300 Series



6" diameter on 4-1/2" base

Standard Bell Alarm

- Loud clanging alarm
 - Weather-proof— enamel and stainless steel
 - Ideal for Marine environment
- | | | |
|--------------|--------|---------|
| 20100 | RBA-12 | 12 volt |
| 20101 | RBA-24 | 24 volt |
| 20102 | RBA-32 | 32 volt |



Water proof back box for bell
20140 Bell Back Box



Piezo Alarm Buzzer

- Loud 85 dB
- Flush or surface mount
- Can be used with any detector

20106 EA-12 12, 24, 32 volt

Alarm Siren

- 125 dB siren sound
- Six selectable siren tones
- Weather proof housing
- Can be used with any detector

20107 EA-12A 12 volt



Visual Indicator Panel

- Black Phenolic with white engraved letters
- Five lights with 10" cable

20030 852 Single engine
3-1/2" x 4-5/8"

Visual Indicator Panel

- Black Phenolic with white engraved letters
- Ten lights with 10" cable

20031 853 Twin engine
4" x 5"



Engine Overheat Detector


- 1/2" male pipe thread
- Installs into pipe plugged hole in engine block
- Activates alarm if water temperature exceeds 200 ° F

20118 212A 12,24,32 volt

Engine Overheat Detector

- Bolt on type
- Bolts to engine block or engine head
- Activates alarm if water temperature exceeds 200 ° F

20116 212 12, 24 32 volt



3-1/4" x 1-3/4"



1-3/4" diameter x 3" high

Bilge Water Level Detector

- Monitors rising bilge water
- No mercury
- Made of rugged ABS and Lexan
- Resists oil, dirt and grease

Remote Fire Detector

- Available in 135° F or 190° F
- Compact size
- Easy two wire installation

20112 204 135°, 12,24,32 volt
20114 204A 190°, 12,24,32 volt



2-1/2" diameter



P. C. Control Board

- Interface for detectors with indicator panels and audible alarm.
- | | | |
|--------------|--------|---------|
| 20020 | 851-12 | 12 volt |
| 20021 | 851-24 | 24 volt |
| 20022 | 851-32 | 32 volt |

Low Oil Pressure Detector

- Activates alarm if oil pressure falls below 10 psi
- 1/8" male pipe thread

20111 202 12,24,32 volt

