



● Up to 280 mA

● Great for marine applications and RVs

● Weighs just 7.7 oz

- Ultra light material is paper thin
- Flexes up to 20° to curve and mold to any roof
- Low profile design
- Up to 280 mA / 5W
- Ideal for topping off batteries and trickle charging
- Permanent installation can be made without drill holes
- Temporary installation with included suction cups

## 5 Watt Semi-Flex Solar Panel

### Shipping Details

Item Number:	56802
UPC Code:	839290005309
Country of Origin:	Vietnam
Shipping size:	16.25 x 13.5 x 2 in
Shipping weight:	2.71lbs
Master Dimension:	19.5 x 14 x 17 in
Master Quantity:	10
Master Weight:	27.1 lbs
Pallet Quantity:	384
HS Code:	8541400022
NMFC:	177010-05
Freight Class:	125

### Specifications

Type	Monocrystalline
Product Dimensions	11.6 x 7.1 x .07 in
Maximum System Voltage	500 V
Current at Pmax	280 mA
Voltage at Pmax	17.82 V
Maximum Power	5 W
Short Circuit Current	302 mA

### Output and Runtimes

<b>Weekly Output - Watts/Amps</b> (based on 7 hours of Sunlight per day)	<b>245 Watts</b> <b>14 Amps</b>
<b>Weekly Run Times*</b>	
Laptop (20-50 watts)	4.9 h
PC (80-150 watts)	1.6 h
Television (70 watts)	3.5 h
CD Player - Radio (35 watts)	7 h
Fan (10 - 50 watts)	4.9 h
Halogen light (100 watts)	2.5 h
Fluorescent light (40 watts)	6.1 h
Coffee Maker (800 watts)	0.3 h

\* Please note our outputs and runtimes are estimated numbers only



Portable



Weatherproof



Easy Installation



Lightweight

